

CIMBAR

Performance Minerals

BARA 200 - Barium Sulfate

BARA 200 is a natural barium sulfate. Cimbar's BARA 200 is designed to meet all the requirements of drilling grade barite. BARA meets or exceeds all API requirements. These properties make BARA 200 barium sulfate the industry standard for quality and performance in oil field applications and a wide range of other end-use applications.

TYPICAL PHYSICAL PROPERTIES

Specific Gravity	4.20 min.
Residue greater than 75 Microns (200 Mesh)	3.0 max.
Water Soluble Alkaline Earth Metals as Calcium	250 mg/kg max.
Particles less than 6 microns	30% max.
Moisture Content	0.10
pH	8

Uses:

- Rubber
- Plastics
- Acoustical compounds
- Friction materials
- Urethane foams
- Mold release agents
- Drilling fluids & other oilfield applications



Post Office Box 250 • Cartersville, Georgia 30120
Customer Service: 800.852.6868 • Fax: 770.607-3799 • www.cimbar.com

Because the conditions of use of this product are beyond seller's control the product is sold without warranty either express or implied and upon condition that the purchaser make its own tests to determine the suitability for purchaser's applications. Purchaser assumes all risk of use and handling of this product. This product will be replaced if defective in manufacture or packaging or if damaged, except for such replacement, seller is not liable for any damages caused by this product or its use. Any data and any statements and recommendations presented herein are believed to be accurate but no guarantee of their accuracy is made. **Rev. 7/09 JHG**

BARA 200